



GXP2110 is a next generation enterprise grade IP phone that features 4 lines, a large 240x120 backlit graphical LCD, 3 XML programmable context-sensitive soft keys, 18 XML programmable BLF extension keys, dual network ports with integrated PoE, and 5-way conference. The GXP2110 delivers superior HD audio quality, rich and leading edge telephony features, personalized information and customizable application service, automated provisioning for easy deployment, advanced security protection for privacy, and broad interoperability with most 3rd party SIP devices and leading SIP/NGN/IMS platforms. It is a perfect choice for enterprise users looking for a high quality, feature rich multi-line IP phone with numerous extension keys.

Feature Highlights

- Large 240x120 pixel backlit graphical LCD display with up to 8 level grayscale
- 4 dual-color line keys (with 4 SIP accounts), 3 XML programmable context-sensitive soft keys, up to 5-way conference, and up to 22 call appearances with 18 dual-color BLF extension keys
- HD wideband audio, superb full-duplex hands-free speakerphone with advanced acoustic echo cancellation and excellent double-talk performance
- Large phonebook (up to 2,000 contacts) and call history (up to 2,000 records)
- Automated personal information service (e.g., local weather, stock, currencies, RSS news, etc), personalized music ring tone/ring back tone/music-on-hold, flexible customizable screen content & format using XML, and advanced Web and enterprise applications integration (pending)
- Dual switched auto-sensing 10/100Mbps network ports with integrated PoE
- Automated provisioning using TR-069 or encrypted XML configuration file, SRTP and TLS for advanced security protection, 802.1x for media access control

Grandstream Networks, Inc. www.grandstream.com

Corporate Headquarter
1297 Beacon Street, 2F
Brookline, MA 02446 USA
Voice: 1-617-566-9300

Dallas Office
2301 W Plano Parkway, Suite 208
Plano, TX 75075 USA
Voice: 1-469-241-0100

Los Angeles Office
1208 John Reed Court,
City of Industry, CA 91745 USA
Voice: 1-626-638-9172

China Office
Bldg#1, No.2 Kefa Rd Science & Technology Park
(Central) Shenzhen, China 518057
Voice: 86-755-2601-4600

Protocols/Standards	SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP/HTTPS, ARP/RARP, ICMP, DNS (A record, SRV, NAPTR), DHCP, PPPoE, TELNET, TFTP, NTP, STUN, SIMPLE, TR-069, 802.1x, IPV6 (pending)
Network Interfaces	Dual switched 10/100Mbps ports with integrated PoE
Graphic Display	Back-lit 240x120 graphical LCD display with up to 8 level grayscale
Feature Keys	4 line keys with dual-color LED and 4 independent SIP accounts, 18 programmable BLF extension keys with dual-color LED, 3 XML programmable context sensitive soft keys, 5 navigation/menu/volume keys, 11 dedicated function keys for: HOLD, SPEAKERPHONE, SEND/REDIAL, TRANSFER, CONFERENCE, MUTE, HEADSET, INTERCOM/PAGING, DO-NOT-DISTURB, PHONEBOOK, and MESSAGE (with LED indicator)
Voice Codec	Support for G.723.1, G.729A/B, G.711 μ /a-law, G.726, G.722 (wide-band), and iLBC, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Telephony Features	Hold, transfer, forward, 5-way conference, busy-lamp-field (BLF), call park, pickup, shared-call-appearance (SCA)/bridged-line-appearance (BLA), downloadable phone book (XML, LDAP, up to 2,000 items), call waiting, call log (up to 2,000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot desking, personalized music ringtones and music on hold, server redundancy and fail-over
HD Audio	Yes, both on handset and speakerphone
Headset Jack	Both RJ9 and 2.5mm jacks for professional and casual use
Base Stand	Yes, allows 2 angle positions
Wall Mountable	Yes
Expansion Module	Allow up to 2 externally attached expansion modules and 112 extra keys
QoS	Layer 2 (802.1Q, 801.2p) and Layer 3 (ToS, DiffServ, MPLS) QoS
Security	User and administrator level passwords, MD5 and MD5-sess based authentication, AES based secure configuration file, SRTP, TLS, 802.1x media access control
Multi-language	Arabic, Croatian, Czech, Dutch, English, French, German, Hebrew, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Slovenian, Simplified Chinese, Turkish, Traditional Chinese
Upgrade/Provisioning	Firmware upgrade via TFTP/HTTP/HTTPS, mass provisioning using TR-069 or encrypted XML configuration file
Power & Green Energy Efficiency	Universal power adapter included: Input: 100-240VAC 50-60Hz; Output: +5VDC, 800mA); Integrated Power-over-Ethernet (802.3af); Max power consumption 2.5W (power adapter) or 3W (PoE)
Physical	Dimension: 252mm (W) x 210mm (L) x 78mm (H); Unit weight: 1.08KG; Package weight: 1.78KG
Temperature and Humidity	32-104°F / 0-40°C, 10-90% (non-condensing)
Package Content	GXP2110 phone, handset with cord, base stand, universal power supply, network cable, Quick Start Guide
Compliance	FCC Part 15 (CFR 47) Class B; EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, EN 60950-1; AS/NZS CISPR 22 Class B, AS/NZS CISPR 24, RoHS; UL 60950 (power adapter)